

Drum & IBC Store - DPU4-1

Backed by our 20 year structural guarantee*

A 2mm pressed steel welded body construction provides the structural strength for this unit, while the roof which is fitted with lifting eyes is manufactured from 3mm mild steel. The two hinged doors are constructed from 2mm mild steel and are fitted with a rod and lever locking mechanism with keyed handle. Constructed from 3mm mild steel, the sump is fully seam welded and fitted with pallet support beams onto which the pallet sits directly. The sump as you would expect complies fully with all current UK regulations relating to sump capacities and the underside is fitted with plinths to eliminate contact with ground and reduce the risk of corrosion. Prior to painting the unit is fully shot blasted to provide a clean and keyed surface.

This model can hold up to 4 x 205ltr or 1 x 1000ltr IBC (1 pallet location) and will accommodate standard 1200mm x 1200mm, 1200mm x 1000mm and 1200mm x 800mm pallets.

*Full details available on request

Chargeable Options:

- Air vents
- Galvanised steel grid mesh
- Galvanised steel pallet channels

Please notify us at the time of ordering if you require any of these options.



SPECIFICATIONS	
Size	1450mm L x 1550mm W x 2175mm H at the highest point on the unit
Internal clear space	1320mm L x 1390mm W x 1425mm H
N ^o of containers	4 x 205ltr or 1 x 1000ltr - vertical
Sump capacity	1470ltr
Colour:	Green RAL 6029
Tare weight	500kg
Type of doors	2 hinged
Type of door lock	Rod & level with a keyed handle
Access aperture	1320mm W x 1390mm H
Paint specification	A high build, quick drying primer/topcoat paint specifically designed for use directly on to metal or bare steel, this paint contains zinc phosphate anti-corrosive pigments and is applied with a minimum dry film thickness of 75 microns.

This unit will be delivered by an HGV, possibly articulated therefore please ensure that a vehicle of this type can access your premises before ordering and advise us accordingly.

You will require an appropriate size/capacity fork lift truck to offload this item from the delivery vehicle. Our standard delivery doesn't include any offloading, but we do offer a chargeable HIAB service, which means the unit can be offloaded in any location that the HIAB vehicle can stand adjacent to. The use of this service doesn't include the levelling of the unit or any responsibility for where you ask for it to be placed on the ground. Any subsequent issues with subsidence or the unit becoming un-level remain your (the customers') responsibility.

The unit must be positioned on a solid level surface, ideally concrete of circa 150mm in depth and 100mm bigger overall than the unit. The purpose of this is to ensure the unit does not settle unevenly when loaded. Empteezy will not accept responsibility for the correction of units which have been settled on uneven or subsiding ground.

