



SATELLITE

S2

S2 is a simple, robust and reliable satellite for decentral and central cleaning.

A new and upgraded version of the legendary S30, the satellite which has been part of System Cleaners' product range for many years.

It is connected to pressurised water from a System Cleaners main station or pump station and operated with a mechanical selector switch

It can rinse, foam and disinfect, and works within the range of 3-40 bar.

HIGHLIGHTS

- Easy to service
- Hygienic design
- High quality materials
- Great operational reliability
- Designed and built according to System Cleaners' renowned principles of simple operation, robust construction and exceptional reliability.

VARIANTS

S2 is available as wall model as well as trolley model.

TECHNICAL SPECIFICATIONS



FOAM

Flow	150 l/min
Dosage **	0.2-6%

DISINFECTION

Flow	7 l/min
Dosage **	0.2-6%

NOZZLES

Standard for rinse (3-8 bar)	10/40
Standard for rinse (10-40 bar)	15/30
Standard for foam	50/200
Standard for disinfection	60/30

OUTLET HOSE*

Water pressure 3-8 bar	3/4", max 15m
Water pressure 10-40 bar	1/2", max 35m

DIMENSIONS

Height	486 mm
Width	336mm
Depth	149 mm
Weight	10 kg

WALL MODEL

TROLLEY MODEL

Height	1300 mm
Width	628 mm
Depth	750 mm
Weight	30 kg

Please note : Requirements when units are in service:

WATER SUPPLY

Connection	external thread 1/2" BSP
Max. temperature	70° C
Min. flow	30 litres/minute
Max. pressure	40 bar

AIR SUPPLY

Connection	ø 6
Min. pressure	5 bar
Max. pressure	10 bar
Min. flow	150 litres/minute

* Applies for model connected to compressed air.

** Depending on product, temperature, viscosity, density and conditions for pressure.

RECOMMENDED SPARE PARTS FOR MAINTAINING A S2



Non-return valve air 1/4"
20-200025



Ball valve 1/2" SS
20-000284



Non-return valve DN 20
20-200175



Dosing valve
20-400053



Air unit
15-010161