



Designed to provide high performance for the cleaning of vertical and non-flat surfaces, the ProKart is perfect for use in food and beverage production areas where mobility on the plant is necessary.

Thanks to the air driven pump is possible to generate a rich and thick foam from a premixed non pressurized solution that provides comprehensive coverage of surfaces along with extended contact time for superior cleaning and disinfection performance.

ProKart requires only a compressed air supply for operation and is very simple to maintain, making it one of the most convenient surface-cleaning solutions of its kind.

MODELS:

ProKart 25Gall (95lt) 5gpm (19lt/min) Santoprene pump, EPDM seal

ProKart 25Gall (95lt) 5gpm (19lt/min) FPM pump, EPDM seal

KEY FEATURES and BENEFITS

- Dry foam
- Equipped with a lance and delivery tube
- No electrical connection required
- Portable

| TECHNICAL FEATURES | |
|------------------------------|--|
| DRIVEN BY | Compressed air |
| AIR PRESSURE | Min 2.7 bar (2.8 kgf / cm ² or 40 psi) Max 5.5 bar (5.6 kgf / cm ² or 80 psi) |
| AIR CONNECTION | Male quick connector SWE/1 |
| PUMP | 5GPM (19l/min) FPM or Santoprene (depending on the model) |
| SOLUTION TYPE | Chemical solution diluted in water |
| SOLUTION TEMPERATURE | Min 5°C (40°F) Max 37°C (100°F) |
| OUTLET HOSE LENGHT | Included 9mt blue (30ft) |
| MAXIMUM TANK CAPACITY | 25Gall (95lt) |
| DELIVERY HOSE | Included 9mt blue |
| FOAM LANCE | Included stainless steel with activator |
| Dimensions | H = 970 mm (38.2") W = 390 mm (15.4") D = 645 mm (25.4") |

DIMENSIONS AND PACKAGING

